<u>Tema Buen</u>

Design: Niels Enevold



Tema Buen is a wall fitting in galvanised steel. Galvanised products are strong and maintenance free. They are shiny at first, but gain patina quickly, resulting in a matt and darker surface.


Tema Buen is available with LED or E27 lamp types. Two LED types are available: downwards only or up/downwards - see specification below.

The shade in UV and impact-resistant polycarbonate comes in clear or opal-white. The clear shade can be equipped with top cover in order to avoid discomfort glare and visibility of the light source.



Te<u>ma Buen - LED</u>

Design: Niels Enevold



LED and driver specifikation:

Luminaire specification:

Material:	Hot-dipped galvanised steel
Wall box:	Cast aluminium
Shade:	Clear or opal white polycarbonate, option for top cover
Connection:	max 2 cables, 2.5 mm ² , into 5 x 6 mm ² terminal block
Classification:	IP66, class I or II
Impact resistance:	IK10
Corrosion class:	C4
Weight:	ca 5 kg
Lamp type:	LED, exchangable

LED and driver specifikation:


LED und unve	i specifikation.		specifikation
LED type:	1 x Bridgelux V8, downwards Only little light upwards;	LED type:	2 x Bridgelux V8, up and downwards Uniform light up and down;
T (1) (upper half of shade can be closed by top cover	T (1) ()	opal-white shade recommended
Total consumption:	6, 8, or 11 W	Total consumption:	11, 15, or 21 W
Operational life:	min 100,000 hours at ta max 25°C, L90B10	Operational life:	min 100,000 hours at ta max 25°C, L90B10
Colour temperature:	2700, 3000, or 4000 Kelvin	Colour temperature:	2700, 3000, or 4000 Kelvin
Energy eff. class:	F	Energy eff. class:	F
Colour rendering:	min 90 Ra	Colour rendering:	min 90 Ra
Colour accuracy:	3 Steps SDCM	Colour accuracy:	3 Steps SDCM
Output ratio:	80% (clear shade)	Output ratio:	48% (opal-white shade)
D (.	
Driver:	LED driver, 250, 350, or 500 mA	Driver:	LED driver, 250, 350, or 500 mA
	Option for dimmable driver		Option for dimmable driver
Operational life:	min 50,000 hours	Operational life:	min 50,000 hours

Product codes:

Tema Buen LED											
Item Nos.	Lam	Lamp type									
6872-	1 x B	1 x Bridgelux V8, 6 W, 250 mA									
6870-	1 x B	1 x Bridgelux V8, 8 W, 350 mA									
6871-	1 x B	1 x Bridgelux V8, 11 W, 500 mA									
6874-	2 x B	2 x Bridgelux V8, 11 W, 250 mA									
6875-	2 x B	2 x Bridgelux V8, 15 W, 350 mA									
6876-	2 x B	2 x Bridgelux V8, 21 W, 500 mA									
	Selec	ct colour, colou	ır temp	erature, etc. in the	table	below.					
Combine with:	Colour		Colo	Colour temperature		Dimming		Classification		Shade	
	9	galvanised	927	2700 K, 90 Ra	V	1-10 V	empty	class I	empty	clear shade	
			930	3000 K, 90 Ra	D	Dali	K	class II	H	top cover	
			940	4000 K, 90 Ra	E	programmable			0	opal-white shade	
Example Order code	6870	-9930H — Ten	na Bue	n, galvanised, 8 W l	ED, 30	000 K 90 Ra, clear s	hade wi	th top cover			

Tema Buen - E27

Design: Niels Enevold



Luminaire specification:

Material:	Hot-dipped galvanised steel
Wall box:	Cast aluminium
Shade:	Clear or opal-white polycarbonate,
	option for top cover
Connection:	max 2 cables, 2.5 mm ² , into 5 x 6 mm ²
	terminal block
Classification:	IP66, class I or II
Impact resistance:	IK10
Corrosion class:	C4
Weight:	ca 5 kg

 Tema Buen E27

 Lamp type:
 max 52 W, max L/Ø: 116/60 mm

Tema Buen							
Item Nos.	Lam	Lamp type					
6071-	E27, max 52 W, max length 116 mm, max diameter 60 mm						
		· · · · ·	-				
	Sele	Select colour in the table below.					
Combine with:	Colour		Shade				
	9	galvanised	empty	clear shade			
			H	top cover			
			0	opal-white shade			
		1	1.		_1		
Example Order code:	6071	-9H = Tema Ruen	nalvanised	E27, clear shade with t	ton cover		

FOCUS-LIGHTING